

File 352:DERWENT WPI 1963-2000/UD=, UM=, & UP=200024

(c) 2000 Derwent Info Ltd

*File 352: Display format changes coming soon. Try them out now in ONTAP File 280. See HELP NEWS 280 for details.

	<u>Set</u>	<u>Items</u>	<u>Description</u>
?S	PN=JP	1247498	
	S1	1	PN=JP 1247498
?T	S1/AB/		

1/AB/1

DIALOG(R)File 352:(c) 2000 Derwent Info Ltd. All rts. reserv.

Abstract (Basic): EP 327963 A

The density of a spray-dried washing agent is raised, without use of liq. granulating agents, by feeding the spray-dried powder, with bulk wt. of at least 350 g/l, continuously into a mixing drum with smooth inner walls, which is either horizontal or at a slight inclination; an axle with radially arranged beaters, the length of which (calc. from the centre of the axle) is 80-98% of the inner radius of the drum, rotates axially in the drum. The rate of rotation of the axle is such that at a residence time of 10-60 secs. and constant powder feed, the Froude number is 50-1200.

The powder may contain 0.5-3 wt. of fine, dry zeolite.

ADVANTAGE - The process is continuous, throughput is high, residence times are short, costs and energy expenditure are low, and the process is flexible.

0/0